



**SAFETY DATA SHEET**  
ROAR 950 EXTREME FINISHING GLAZE

Page: 1

Compilation date: 06/06/2017

Revision No: 1

**Section 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

**Product name:** ROAR 950 EXTREME FINISHING GLAZE

**Product code:** 950-10 950-40

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Use of substance / mixture:** PC31: Polishes and wax blends.

**1.3. Details of the supplier of the safety data sheet**

**Company name:** Roar Advanced Finishing Ltd

Unit 2c Bradley Park

High Holborn Road

Ripley

Derbyshire

DE5 3NW

United Kingdom

**Tel:** 01773 743492

**Email:** [rob@roar-polishing.com](mailto:rob@roar-polishing.com)

**1.4. Emergency telephone number**

**Emergency tel:** 01773 743492

(office hours only)

**Section 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification under CLP:** -: EUH066; -: EUH208

**Most important adverse effects:** Repeated exposure may cause skin dryness or cracking. Contains 1,2-benzisothiazolin-3-one. May produce an allergic reaction.

**2.2. Label elements**

**Label elements:**

**Hazard statements:** EUH066: Repeated exposure may cause skin dryness or cracking.

EUH208: Contains 1,2-benzisothiazolin-3-one. May produce an allergic reaction.

**2.3. Other hazards**

**PBT:** This product is not identified as a PBT/vPvB substance.

**Section 3: Composition/information on ingredients**

[cont...]

**SAFETY DATA SHEET**  
ROAR 950 EXTREME FINISHING GLAZE

Page: 2

**3.2. Mixtures**

**Hazardous ingredients:**

CALCINED ALUMINA - REACH registered number(s): 01-2119529248-35

EINECS	CAS	PBT / WEL	CLP Classification	Percent
215-691-6	1344-28-1	Substance with a Community workplace exposure limit.	-	10-30%

HYDROCARBONS, C11-C13, ISOALKANES, <2% AROMATICS - REACH registered number(s): 01-2119456810-40

920-901-0	-	-	Asp. Tox. 1: H304; -: EUH066	10-30%
-----------	---	---	------------------------------	--------

HYDROCARBONS, C16-C20, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS - REACH registered number (s): 01-21194557735-29

919-029-3	-	Substance with a Community workplace exposure limit.	Asp. Tox. 1: H304; -: EUH066	1-10%
-----------	---	--	------------------------------	-------

ANHYDROUS ALUMINIUM SILICATE

296-473-8	92704-41-1	Substance with a Community workplace exposure limit.	-	<1%
-----------	------------	--	---	-----

**Non-classified ingredients:**

HYDROCARBONS, C11-C14, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS - REACH registered number (s): 01-2119456620-43

EINECS	CAS	PBT / WEL	CLP Classification	Percent
926-141-6	-	-	Asp. Tox. 1: H304	1-10%

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS - REACH registered number (s): 01-21194557273-39

918-481-9	64742-48-9	-	Asp. Tox. 1: H304; -: EUH066	1-10%
-----------	------------	---	------------------------------	-------

WHITE MINERAL OIL 2 - REACH registered number(s): 01-2119487078-27

232-455-8	8042-47-5	-	-	1-10%
-----------	-----------	---	---	-------

**Section 4: First aid measures**

**4.1. Description of first aid measures**

**Skin contact:** Wash immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes.

**Ingestion:** Wash out mouth with water.

**Inhalation:** Consult a doctor.

**4.2. Most important symptoms and effects, both acute and delayed**

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be irritation of the throat.

**Inhalation:** No symptoms.

[cont...]

**SAFETY DATA SHEET**  
ROAR 950 EXTREME FINISHING GLAZE

Page: 3

**Delayed / immediate effects:** No symptoms.

**4.3. Indication of any immediate medical attention and special treatment needed**

**Immediate / special treatment:** Not applicable.

**Section 5: Fire-fighting measures**

**5.1. Extinguishing media**

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

**5.2. Special hazards arising from the substance or mixture**

**Exposure hazards:** In combustion emits toxic fumes.

**5.3. Advice for fire-fighters**

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

**Section 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

**Personal precautions:** Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-side up to prevent the escape of liquid.

**6.2. Environmental precautions**

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

**6.3. Methods and material for containment and cleaning up**

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

**6.4. Reference to other sections**

**Reference to other sections:** Refer to section 8 of SDS.

**Section 7: Handling and storage**

**7.1. Precautions for safe handling**

**Handling requirements:** Ensure there is sufficient ventilation of the area.

**7.2. Conditions for safe storage, including any incompatibilities**

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed.

**Suitable packaging:** Must only be kept in original packaging.

**7.3. Specific end use(s)**

**Specific end use(s):** No data available.

[cont...]

**SAFETY DATA SHEET**  
ROAR 950 EXTREME FINISHING GLAZE

Page: 4

**Section 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Hazardous ingredients:**

**HYDROCARBONS, C11-C13, ISOALKANES, <2% AROMATICS**

**Workplace exposure limits:**

**Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
EU	1200mg/m3	-	-	-

**HYDROCARBONS, C16-C20, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS**

UK	5 mg/m3	-	-	-
----	---------	---	---	---

**ANHYDROUS ALUMINIUM SILICATE**

UK	10 mg/m3	-	-	-
----	----------	---	---	---

**DNEL/PNEC Values**

**Hazardous ingredients:**

**CALCINED ALUMINA**

Type	Exposure	Value	Population	Effect
DNEL	Inhalation	3 mg/m3	Workers	Local

**8.2. Exposure controls**

**Engineering measures:** The floor of the storage room must be impermeable to prevent the escape of liquids.

**Respiratory protection:** Respiratory protection not required.

**Hand protection:** Protective gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

**Environmental:** The floor of the storage room must be impermeable to prevent the escape of liquids.

**Section 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

**State:** Liquid

**Colour:** White

**Odour:** Characteristic odour

**Evaporation rate:** Slow

**Oxidising:** Non-oxidising (by EC criteria)

**Solubility in water:** Miscible

**Also soluble in:** Most organic solvents.

**Viscosity:** Highly viscous

**Kinematic viscosity:** 35,000cps

[cont...]

**SAFETY DATA SHEET**  
ROAR 950 EXTREME FINISHING GLAZE

Page: 5

**Viscosity test method:** Brookfield @20degC

**Boiling point/range°C:** No data available.

**Melting point/range°C:** No data available.

**Flammability limits %: lower:** No data available.

**upper:** No data available.

**Flash point°C:** 65

**Part.coeff. n-octanol/water:** No data available.

**Autoflammability°C:** No data available.

**Vapour pressure:** No data available.

**Relative density:** 1.10

**pH:** 7 - 9

**VOC g/l:** 108

**9.2. Other information**

**Other information:** No data available.

**Section 10: Stability and reactivity**

**10.1. Reactivity**

**Reactivity:** Stable under recommended transport or storage conditions.

**10.2. Chemical stability**

**Chemical stability:** Stable under normal conditions.

**10.3. Possibility of hazardous reactions**

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

**10.4. Conditions to avoid**

**Conditions to avoid:** Heat.

**10.5. Incompatible materials**

**Materials to avoid:** Strong oxidising agents. Strong acids.

**10.6. Hazardous decomposition products**

**Haz. decomp. products:** In combustion emits toxic fumes.

**Section 11: Toxicological information**

**11.1. Information on toxicological effects**

**Hazardous ingredients:**

**HYDROCARBONS, C11-C13, ISOALKANES, <2% AROMATICS**

DERMAL	RBT	LD50	>5000	mg/kg
ORAL	RAT	LD50	>5000	mg/kg

**Excluded hazards for substance:**

Hazard	Route	Basis
--------	-------	-------

[cont...]

# SAFETY DATA SHEET

ROAR 950 EXTREME FINISHING GLAZE

Page: 6

Acute toxicity (ac. tox. 4)	-	No hazard: calculated
Acute toxicity (ac. tox. 3)	-	No hazard: calculated
Acute toxicity (ac. tox. 2)	-	No hazard: calculated
Acute toxicity (ac. tox. 1)	-	No hazard: calculated
Skin corrosion/irritation	-	No hazard: calculated
Serious eye damage/irritation	-	No hazard: calculated
Respiratory/skin sensitisation	-	No hazard: calculated
Germ cell mutagenicity	-	No hazard: calculated
Carcinogenicity	-	No hazard: calculated
Reproductive toxicity	-	No hazard: calculated
STOT-single exposure	-	No hazard: calculated
STOT-repeated exposure	-	No hazard: calculated
Aspiration hazard	-	No hazard: calculated

## Symptoms / routes of exposure

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be irritation of the throat.

**Inhalation:** No symptoms.

**Delayed / immediate effects:** No symptoms.

## Section 12: Ecological information

### 12.1. Toxicity

#### Hazardous ingredients:

##### HYDROCARBONS, C11-C13, ISOALKANES, <2% AROMATICS

Daphnia magna	48H EC50	1000	mg/l
---------------	----------	------	------

##### HYDROCARBONS, C16-C20, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

FISH	96H LC50	1028	mg/l
MARINE ALGAE (Skeletonema costatum)	72H ErC50	3196	mg/l
MARINE ALGAE (Skeletonema costatum)	72H IC50	3198	mg/l

##### ANHYDROUS ALUMINIUM SILICATE

FISH	96H LC50	>1000	mg/l
------	----------	-------	------

### 12.2. Persistence and degradability

**Persistence and degradability:** Biodegradable.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No bioaccumulation potential.

[cont...]

**SAFETY DATA SHEET**  
ROAR 950 EXTREME FINISHING GLAZE

Page: 7

**12.4. Mobility in soil**

**Mobility:** Readily absorbed into soil.

**12.5. Results of PBT and vPvB assessment**

**PBT identification:** This product is not identified as a PBT/vPvB substance.

**12.6. Other adverse effects**

**Other adverse effects:** Negligible ecotoxicity.

**Section 13: Disposal considerations**

**13.1. Waste treatment methods**

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**Recovery operations:** Not applicable.

**Waste code number:** 08 04 12

**Disposal of packaging:** Not applicable.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**Section 14: Transport information**

**Transport class:** This product does not require a classification for transport.

**Section 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Specific regulations:** Not applicable.

**15.2. Chemical Safety Assessment**

**Section 16: Other information**

**Other information**

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** EUH066: Repeated exposure may cause skin dryness or cracking.

EUH208: Contains <name of sensitising substance>. May produce an allergic reaction.

H304: May be fatal if swallowed and enters airways.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.